



# Optimo Style 30-76

Lightweight  
Standard Zoom



## Specifications

Zoom ratio	2.5x
Focal Length	30 - 76 mm
Aperture	f/2.6 – T2.8
Close Focus	2 ft – 0.6 m
Internal Focus	Yes
Image coverage	S35+: 31.4 mm diagonal
Weight (approx.)	4.2 lbs – 1.92 kg
Length	186 mm
Front diameter	114 mm

## MAIN FEATURES

- Constant T2.8 across entire zoom range
- Well controlled distortion with no breathing
- Compact and very light: 4.2 lbs - 1.92kg. Ideal for handheld, steadicam, compact gimbals
- Superb image quality from open aperture
- Color reproduction matches the highly acclaimed OPTIMO lens series
- Internal focus, internal zoom, constant lens volume
- Precise and ergonomic focus ring with zoom scale rotation of 320 degrees and over 20 focus witness marks (no interchangeability of focus rings from feet to meters)
- Compatible with ASU servo unit (integrated motors for FTZ remote control through industry standard control systems)
- Compatible with Optimo 1.4x and 2x extenders
  - 42 - 110 mm T4 (with 1.4x)
  - 60 - 152 mm T5.6 (with 2x)
- Adapted to extreme production environments (passive athermalisation from -20°C to +40°C)
- PL mount lens. Easily interchangeable to PV or Canon EF mounts

## Available accessories



PV/EF Mounts



ASU



Extenders or  
Format Adapters  
1.4x & 2x

## Field of view for 22x16 mm

Focal Length	30 mm	76 mm
Horizontal angular field of view	40.2°	16.4°
Object dimensions at MOD (mm)	321x232	126x92